

1. PRODUCT NAME  
Asphalt Binder Plus

2. MANUFACTURER  
SealMaster  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-395-7325  
Fax: 419-626-5477  
www.sealmaster.net

*Additional Plant Locations:*  
SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone us at 1-800-395-7325  
or visit our website at  
www.sealmaster.net to find the  
location near you.

3. PRODUCT DESCRIPTION &  
BENEFITS  
Asphalt Binder Plus is a polymer modified anionic asphalt emulsion designed for use as a recycling agent, rejuvenator, road crack sealant, and tack coat. Asphalt Binder Plus exceeds the ISSA requirements for SS1H.

*Basic Uses:* Recycling agent, rejuvenator, road crack sealant, tack coat.

*Sizes:* Available in bulk, 55-gallon drums, and 5-gallon pails.

*Color:* Dries Black.

*Limitations:* Asphalt Binder Plus shall not be applied when temperature is expected to drop below 50°F within a 24 hour period after application.

4. TECHNICAL DATA  
Asphalt Binder Plus meets and exceeds the chemical composition and performance requirements of ASTM D977 and AASHTO M140.

*Environmental Considerations:*  
Asphalt Binder Plus is an environmentally friendly water based asphalt emulsion containing less than 150 grams per liter volatile organic content (VOC).

*Physical/Chemical Properties:*  
Asphalt Binder Plus meets the

following specifications when tested in accordance with ASTM D140 and ASTM D244 test procedures (see chart below).

5. INSTALLATION  
Surface must be cleaned of dust, dirt and debris.

*Methods:* Asphalt Binder Plus can be applied by spray or brush.

*Mixing/Application Procedures:*  
• *Recycling Agent For Infrared Patching:* Use material as is. Dilution is not required.

• *Fog Seal or Rejuvenator:* Dilute 1 to 1 with water and apply to old oxidized pavement to replenish the asphalt binder that is lost through aging, oxidation, and weathering. Apply by spray at a rate of .06 to .10 gallons of mixed material per square yard (.03 to .05 concentrate Asphalt Binder Plus per square yard). Do not apply to smooth pavement surfaces. Do not over apply and create a slick surface. Pavement must have porosity and profile to maintain friction for vehicles.

• *Tack Coat For Patching or Paving:* Dilute 1 to 1 with water. Apply by spray or brush. Apply at a rate of .06 to .10 gallons of mixed material per square yard (.03 to .05 concentrate).

*Estimating Material Requirements:*  
To estimate gallons of Asphalt Binder Plus required to cover a specific area, use the following coverage rates:

• *Recycling Agent For Infrared Patching:* Indefinite. Dependent upon material requirements.

• *Fog Seal or Rejuvenator:* .03 to .05 gallons per square yard.

• *Tack Coat For Patching or Paving:* .03 to .05 gallons per square yard.

6. AVAILABILITY & COST

*Availability:* Asphalt Binder is supported by a national network of SealMaster facilities along with a national network of professional applicators.

*Cost:* Cost information can be obtained from a local applicator. Contact SealMaster for the representative in your area.

7. WARRANTY  
SealMaster Industries warrants that Asphalt Binder meets the chemical composition and performance requirements set forth in section 4. Liability to the buyer or user of this product is limited to the replacement value of the product only.

## Chemical & Physical Analysis

*Tests On Emulsion:*

Viscosity, Saybolt Furol at 77°F (25°C), s .....	36
Storage Stability Test, 24-h, % .....	1
Cement Mixing Test, % .....	< 2%
Sieve Test, % .....	0.013
Residue by distillation, % .....	65% ± 2%

*Test On Residue:*

Penetration, 77°F (25°C) 100g, 5s .....	55
Ductility, 77°F (25°C) 5 cm/min, cm .....	> 150
Softening Point, R&B, °F .....	> 130
Toughness, inch-pounds .....	> 80
Tenacity, inch-pounds .....	> 60
Solubility in trichlorethylene, % .....	> 97.5

# Asphalt Binder Plus

## 8. TECHNICAL SERVICES

*Manufacturer:* Complete product specifications, material safety data sheets, and technical assistance is available from SealMaster.

*Professional Applicators:* Your local applicator is available to provide on-site inspections and recommendations to meet your specific needs.

## 9. FILING SYSTEMS

- SealMaster Online Specifications at [www.sealmaster.net](http://www.sealmaster.net)
- Complete SealMaster Product and Equipment Catalog Available
- Sweet's Catalog
- Sweet's CD
- Sweet's Online
- Sweet's Directory

The statements made on this specification sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

Form No.: SMT-231

Date: 5/03

Copyright © 2003, SealMaster Industries, Inc. All rights reserved.

SealMaster Industries, Inc.  
2520 South Campbell ST.  
Sandusky, OH 44870

Phone: 1-800-395-7325  
FAX: 1-419-626-5477

[www.sealmaster.net](http://www.sealmaster.net)