

1. PRODUCT NAME

SealMaster ColorPave
Acrylic Colorized
Pavement Sealer

2. MANUFACTURER

SealMaster
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-395-7325
Fax: 419-626-5477
www.sealmaster.net

Additional Plant Locations:
SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone us at 1-800-395-7325
or visit our website at
www.sealmaster.net to find the
location near you.

3. PRODUCT DESCRIPTION & BENEFITS

SealMaster ColorPave is a premium quality 100% acrylic emulsion pavement sealer fortified with sand for slip resistance. SealMaster ColorPave is available in several attractive earthtone colors.

IMPORTANT: Do not apply to pavement surfaces that have previously been sealed with coal tar or asphalt based sealers.

Basic Uses: SealMaster ColorPave is designed to protect and beautify asphalt pavement surfaces including driveways, parking lots, walkways, golf cart paths, jogging/bike paths, amusement parks, recreational surfaces, and more.

Composition: SealMaster ColorPave is a 100% acrylic emulsion fortified with sand for slip resistance. SealMaster ColorPave is supplied in a ready to use form.

Sizes: SealMaster ColorPave is available in 4,000 gallon bulk tankers, 55-gallon drums, and 5-gallon pails.

Color: Mocha Gray, Brickyard Red, Sahara Beige, and Forest Green.

Limitations: SealMaster ColorPave

shall not be applied when temperature is expected to drop below 50°F at any time within a 24 hour period after application.

4. Physical/Chemical Properties:
SealMaster ColorPave is a premium quality pavement coating that meets the following material requirements when tested in accordance with ASTM D 714, ASTM D 661, ASTM D 772, ASTM D 3723, ASTM D 2369, ASTM D 522, ASTM D 4585 procedures. (see chart below)

Environmental Considerations:
SealMaster ColorPave does not contain asbestos. SealMaster ColorPave is an environmentally friendly water based pavement coating containing less than 150 grams per liter volatile organic content (VOC).

5. INSTALLATION

Surface must be cleaned and free from all loose material and dirt. Pavement surface repairs should be made with a suitable hot or cold asphalt mix. Fill cracks with suitable SealMaster cold applied crack filler. Scrub and clean grease, oil, and gasoline spots with soap and water.

Methods: SealMaster ColorPave shall be applied by squeegee application. Self-propelled squeegee equipment and hand squeegees are acceptable.

Mixing Procedures:

SealMaster ColorPave is a ready to use product that contains sand. Simply stir material and apply.

Application: For optimum performance and durability apply two coats of SealMaster ColorPave. A third coat of SealMaster ColorPave may be applied to high traffic areas such as entrances, exits, and drive lanes.

Application Rate: Apply SealMaster ColorPave at a rate of .13 to .15 gallon per square yard (60 to 70 square feet per gallon) per coat.

Estimating Material Requirements:
Typically, one gallon of SealMaster ColorPave will cover approximately 60 to 70 square feet (6.7 to 7.8 square yards) per coat.

Note: Coverage rates may vary due to pavement age and porosity. Extremely porous pavement will result in reduced coverage rates.

Precautions: Both surface and ambient temperature shall be a minimum of 50°F. Temperature shall not drop below 50°F in a 24 hour period following application. New asphalt surfaces should be allowed to cure a minimum of four weeks under ideal weather conditions (70°F) before applying SealMaster ColorPave. Keep Out Of Reach

TEST	SPECIFICATIONS	RESULT
Material	Material shall be homogenous and show no separation or coagulation that cannot be overcome by moderate stirring.	PASSES
Chem. & Physical Analysis		
- Non Volatiles %	60 - 65%	PASSES
- Ash Non Volatiles %	65 - 70%	PASSES
- Specific Gravity 25°C	1.4 Minimum	PASSES
Drying Time	8 Hr. Max.	PASSES
Adhesion & Resistance to Water	No Absorption or Loss of Adhesion	PASSES
Resistance to Heat	No Blistering or Sagging	PASSES
Flexibility	No Cracking or Flaking	PASSES
Resistance to Impact	No Chipping, Flaking or Cracking	PASSES

SealMaster ColorPave® Acrylic Colored Pavement Sealer

Of Children. Do not store unopened drums or pails in freezing temperatures.

6. AVAILABILITY & COST

Availability: SealMaster ColorPave is supported by a nationwide network of SealMaster manufacturing facilities along with a national network of qualified applicators.

Cost: Cost information can be obtained from a local SealMaster ColorPave applicator. Contact SealMaster for the SealMaster ColorPave representative in your area.

7. WARRANTY

SealMaster Industries warrants that SealMaster ColorPave meets the chemical composition and performance requirements set forth in section 4. Liability to the buyer or user of this product is limited to the replacement value of the product only.

8. MAINTENANCE

Periodic pavement sweeping will ensure optimum product service life.

9. TECHNICAL SERVICES

Manufacturer: Complete product specifications, material safety data sheets, and technical assistance is available from SealMaster.

Professional Applicator: Your local SealMaster ColorPave applicator is available to provide on-site inspections and recommendations to meet your specific needs.

10. FILING SYSTEMS

- Sweet's Catalog
- Sweet's CD
- Sweet's Online
- Sweet's Directory
- SealMaster Online Specification at www.sealmaster.net
- Complete SealMaster Product and Equipment Catalog Available

The statements made on this specification sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

Form No.: SMT-160

Revised: 5/03

Supersedes: SMT-43 (4/99), SMT-160 (7/01), SMT-160 (10/01)

Copyright © 2003, SealMaster Industries, Inc. All rights reserved.

SealMaster Industries, Inc.
2520 South Campbell ST.
Sandusky, OH 44870

Phone: 1-800-395-7325

FAX: 1-419-626-5477

www.sealmaster.net