

1. PRODUCT NAME
GatorPave

2. MANUFACTURER
SealMaster
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-395-7325
Fax: 419-626-5477
www.sealmaster.net

Additional Plant Locations:
SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone us at 1-800-395-7325 or visit our website at www.sealmaster.net to find the location near you.

3. PRODUCT DESCRIPTION & BENEFITS

GatorPave is a single component, highly filled polymer modified asphalt emulsion that is designed to fill and repair "alligatored" and cracked areas in asphalt pavement surfaces. GatorPave is a cold-applied, easy to use patching material. GatorPave is an economical solution for alligatored areas.

Basic Uses: GatorPave is designed for patching alligatored and cracked areas in asphalt pavement surfaces including parking lots, driveways, and roadways.

Composition: GatorPave is a polymer modified asphalt emulsion fortified with fibers, rubber, and aggregate to provide excellent filling and flexural characteristics.

Sizes: GatorPave is available in 5-gallon and 55-gallon containers.

Color: Dries black.

Limitations: GatorPave shall not be applied when temperature is expected to drop below 50°F at any time within a 24 hour period immediately following application.

4. TECHNICAL DATA

Environmental Considerations: GatorPave is a non-hazardous, environmentally friendly,

waterbased patching material containing less than 150 grams per liter volatile organic content (VOC).

Physical/Chemical Properties: GatorPave meets the following material requirements when tested in accordance with ASTM D140, ASTM D466, ASTM D529, ASTM D2939, and ASTM D244 procedures. (see chart below)

5. INSTALLATION

Alligatored and cracked areas must be cleaned of all dirt, debris, and vegetation prior to application of GatorPave.

Methods: GatorPave shall be spread over repair areas with squeegee or trowel.

Mixing Procedures: Stir material thoroughly. GatorPave is a ready to use material. Do not dilute.

Application: Spread GatorPave patch material over area to be repaired and squeegee or trowel flush to adjoining pavement. Allow material to dry before opening to traffic.

Estimating Material Requirements: GatorPave coverage rate is dependent upon pavement

surface conditions, and width and depth of cracks. A small test patch area may be required to establish overall material usage.

Precautions: Both surface and ambient temperature shall be a minimum of 50°F. Temperature shall not drop below 50°F in a 24 hour period following application. Keep Out Of Reach Of Children. Do not store unopened containers in freezing temperatures.

6. AVAILABILITY & COST

Availability: GatorPave is supported by a national network of SealMaster facilities along with a national network of professional applicators.

Cost: Cost information can be obtained from a local applicator. Contact SealMaster for the name of the applicator in your area.

7. WARRANTY

SealMaster Industries warrants that GatorPave meets the chemical composition and performance requirements set forth in section 4. Liability to the buyer or user of this product is limited to the replacement value of the product only.

Chemical & Physical Analysis

Classification	Polymer Modified Asphalt Emulsion
Color.....	Black when dry
Non-Volatiles (%)	73%
Ash (Non-Volatiles).....	54%
Specific Gravity	1.39
Drying Time...	Dependant upon material depth
Adhesion & Resistance to Water	Non Penetration or Loss of Adhesion
Resistant to Heat.....	No Blistering or Sagging
Flexibility	No Cracking or Flaking
Resistance to Impact	No Chipping, Flaking, or Cracking

GatorPave

9. TECHNICAL SERVICES

Manufacturer: Complete product specifications, material safety data sheets, and technical assistance is available from SealMaster.

Professional Applicators: Your local GatorPave applicator is available to provide on-site inspections and recommendations to meet your specific needs.

10. FILING SYSTEMS

- SealMaster Online Specification at www.sealmaster.net
- Complete SealMaster Product and Equipment Catalog Available
- Sweet's Catalog
- Sweet's CD
- Sweet's Online
- Sweet's Directory

The statements made on this specification sheet are believed to be true and accurate and are intended to provide a guide for approved application practices. As workmanship, weather, construction, condition of pavement, tools utilized, and other variables affecting results are all beyond our control, the manufacturer warrants only that the material conforms to product specifications and any liability to the buyer or user of this product is limited to the replacement value of the product only. The manufacturer expressly disclaims any implied warranties of merchantability or fitness for a particular purpose. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

Form No.: SMT-204
Revised: 10/01
Supersedes: SMT-25 (4/99)

Copyright © 2001, SealMaster Industries, Inc. All rights reserved.

SealMaster Industries, Inc.
2520 South Campbell ST.
Sandusky, OH 44870

Phone: 1-800-395-7325
FAX: 1-419-626-5477

www.sealmaster.net