



Stripe-Rite

CMT - 14

Revised: 6/03

1. PRODUCT NAME:
Stripe-Rite

2. MANUFACTURER:
SealMaster
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-395-7325
Fax: 419-626-5477
www.sealmaster.net

Additional Plant Locations:
SealMaster has a nationwide network of manufacturing and distribution facilities.

Phone us at 1-800-395-7325
or visit our website at
www.sealmaster.net to find the
location near you.

3. PRODUCT DESCRIPTION &
BENEFITS:
Stripe-Rite is a 100% acrylic clear
drying emulsion primer for line
striping. Stripe-Rite is applied prior
to SportMaster Line Paint to fill the
minor voids between the masking
tape and the court surface to
assure crisp, razor sharp lines.

Color: Milky White. Clear when
dried.

Uses: For priming line markings on
any bituminous, concrete or color
coated surface.

4. SURFACE PREPARATION:
Pavement Surface must be
cleaned of dust, dirt, debris and all
loose material.

5. APPLICATION:
Stripe-Rite can be rolled, brushed
or sprayed with low pressure
spraying equipment. Allow Stripe-
Rite to dry completely before
applying SportMaster Line Paint.

6. IMPORTANT:
Stir before using. Temperatures must
be above 50°F. both during
application and for a period of at
least 24 hours after application. Do
not apply if rain is imminent or
forecast. Keep from freezing. Close
container when not in use.

7. DRYING TIME:
Thirty to sixty (30 to 60) minutes

under optimum drying conditions.
Indoor applications are substantially
affected by temperature and
available ventilation and will dry
more slowly.

8. COVERAGE:
450 to 500 lineal feet of 2 inch line
per gallon.

9. CLEAN-UP:
Wash sprayers, tools, etc. in water
before material dries.

10. CAUTION:
Do not store in direct sunlight or
where temperatures exceed 100°F.
Do not apply if rain is imminent or
forecast. Keep from freezing. Close
container when not in use.

11. WARRANTY:
The statements made on this
technical bulletin are believed to
be true and accurate, and are
intended to provide a guide for
approved construction practices.
SealMaster® does not make nor
does it authorize any agent or
representative to make any
warranty, express or implied,
concerning this material, as
workmanship, weather,
construction, equipment utilized

and other variables affecting results
are all beyond our control. SealMaster® warrants only that the
material conforms to product
specifications and any liability to
the buyer or user of this product is
limited to the replacement value
of the product only. In no event
shall SealMaster® be liable for any
injury, loss or damage, either direct
or incidental, special or
consequential, however arising, in
connection with material or
equipment furnished or work
performed. SealMaster® shall not,
in any manner, be liable for any
defects, variations or change in
condition in the substructure over
which its products are installed.

Copyright© 2003, SealMaster
Industries, Inc. All rights reserved.

SportMaster is a division of:
SealMaster Industries, Inc.
P.O. Box 2277
Sandusky, OH 44870

Phone: 1-800-395-7325
FAX: 1-419-626-5477

www.sportmaster.net

Chemical Characteristics:

	% Weight (Nominal)
Acrylic Emulsion	38.0
Hiding Pigment.....	0.0
Mineral Inert Fillers.....	7.0
Film Former, Additives	1.5
Water.....	50.0

Product Data:

Type	Acrylic Emulsion
Weight per gallon at 77°F.....	8.9 ± 5
% Non Volatile Material.....	29 ± 2
Viscosity at 77°F (Kreb's Units).....	80-85
Odor	Slight Ammonia
Flammability.....	Non-Flammable
Flash Point.....	None
Effects of Freezing	Damaging
Storage Life	One Year
Colors.....	Milky White, clear when dry