

# MATERIAL SAFETY DATA SHEET

(In compliance with OSHA Regulation 29 CFR 1910.1200 - Hazard Communication)

<b>IDENTITY:</b> Line Block-Out Paint Product No. M1260
--

<i>SECTION I - Manufacturer / Product Information</i>	
<b>Manufacturer's Name:</b> SealMaster Industries, Inc.	<b>Emergency Telephone No.:</b> Chemtrec: 1-800-424-9300
<b>Address:</b> 2520 South Campbell Street Sandusky, Ohio 44870	<b>Telephone Number for Information:</b> 1-419-626-4375
<b>Date Prepared:</b> July 5, 1995	

<i>SECTION II - Hazardous Ingredients / Identity Information</i>				
Hazardous Components: Specific Chemical Identity; Common Name, CAS No.)	Exposure Limits		Other Limits Recommend.	% (Optional)
<b>Non-Toxic Pigments/Extenders</b>	<b>OSHA PEL - (1)</b>	<b>ACGIH TLV - (2)</b>		<b>Total % 28-30</b>
Silicon Dioxide dust SiO <sub>2</sub> - (3) CAS #14808-60-7	0.1 mg / m <sup>3</sup>			
Ethylene Glycol (*) HOCH <sub>2</sub> CH <sub>2</sub> OH CAS#107-21-1		50 ppm		1.0-1.5
Texanol (Ester Alcohol) 2,2,4-trimethyl-1,3 pentanediol monoisobutyrate CAS #25265-77-4	Not est.			0.7-0.8
Vinyl Acetate Monomer - (4) CAS #108-05-4		10 ppm		< 0.5
(*) Indicate toxic chemical subject to the reporting requirement of section 313 of SARA Title III and 40 CFR 372 (Code of Federal Regulations). (A chemical or chemical category listed by the EPA is subject to toxic chemical release reporting under the Emergency Planning and Community Right-To-Know Act of 1986).				
(1) (OSHA Permissible Exposure Limit) - These limits express the permissible maximum amount of a chemical to which a person may be exposed. The concentrations listed refer to airborne exposure, as might occur (via mist), which is unlikely to form with this product in view of its properties and intended use.				
(2) (American Conference of Governmental Industrial Hygienists' Threshold Limit Value) - This value is expressed in parts per million. The TLV is the concentration of substance in the air that can be breathed for five consecutive eight hour workdays (40-hour work week) by most people, without harmful effects.				
(3) The silicon dioxide dust listed as a hazardous ingredient, is based on OSHA regulations for respirable (airborne) dust. Since this product is a wet application item, there is virtually no hazard associated with its use in its original form. There would be potential hazards associated with silicon dioxide during operations such as sandblasting and scarification.				
(4) Formulation contains less than 0.129% residual monomers, and less than 0.026% formaldehyde.				

### **SECTION III - Physical / Chemical Characteristics**

**Boiling Point:** 100<sup>0</sup> Celsius (212<sup>0</sup> Fahrenheit)

**Specific Gravity (Water = 1):** 1.24-1.26

**Vapor Pressure (mm Hg):** (I) Is nearly equal to the vapor pressure of water.

**Melting Point:** N/A

**Vapor Density:** Lighter than air.

**Evaporation Rate (Butyl Acetate = 1):** More than 1.0; approximately 1.8 at 25<sup>0</sup> Celsius.

**Solubility in Water:** The ethylene glycol portion is water soluble. The remainder of the formulation is not water soluble, but is water dispersible in its liquid state. After drying, the paint film is no longer water soluble to a significant extent.

**Appearance:** Gray liquid

**Odor:** Mild odor of ethylene glycol, characteristic of latex odor.

(I) The vapors off this product are at least 90% water from 0<sup>0</sup> Celsius - 100<sup>0</sup> Celsius

### **SECTION IV - Fire and Explosion Hazard Data**

**HMIS Rating:** 0

**Flash Point (Method Used):** Non Combustible

**Flammable Limits in Air:** Not Applicable.

**Extinguishing Media:** Foam, CO<sub>2</sub>, dry chemical, water fog, other.

**Special Fire Fighting Methods:** Full protective equipment, including self-contained breathing apparatus, to be worn.

**Unusual Fire & Explosion Hazards:** Not Applicable.

### **SECTION V - Reactivity Data**

**HMIS Rating:** 0

**Stability:** Good storage stability between 5<sup>0</sup> Celsius and 50<sup>0</sup> Celsius.

**Conditions to Avoid:** Keep from freezing and extreme heat.

**Incompatibility (Materials to Avoid):** Strong acids or bases, cationic emulsions, or multivalent salts (e.g., magnesium or calcium salts) will cause coagulation.

**Hazardous Decomposition or Byproducts:** Combustion may yield carbon monoxide and/or carbon dioxide, and traces of monomer, as well as other toxic pyrolysis products.

**Hazardous Polymerization:** Will not occur

**SECTION VI - Health Hazard Data**

**HMIS Rating:** 1

**Primary Routes of Exposure:**

**Inhalation:** Yes - Texanol and ethylene glycol from curing paint film; or dust from sandblasting.

**Eye Contact:** Yes

**Skin Contact:** No

**Ingestion:** Yes

**Health Hazards ( Acute & Chronic):** (Acute): Dizziness, weakness, nausea, headache.  
(Chronic): Gastrointestinal irritation - Prolonged or repeated exposure to high vapor concentrations may cause damage to kidneys, liver, lungs, blood, or central nervous system. Repeated ingestion may cause liver damage.

**Signs and Symptoms of Exposure:**

**Inhalation:** Vapor could cause headache, irritation to nose and throat, dizziness, weakness and nausea.

**Eye:** Irritation from vapor or liquid.

**Skin:** Not easily absorbed - prolonged or repeated contact may be mildly irritating to the skin.

**Ingestion:** Can cause nausea, vomiting, diarrhea.

**Medical Conditions Generally Aggravated by Exposure:** None known.

**Carcinogenicity: National Toxicology Program (NTP):** No

**International Agency for Research on Cancer (IARC) Monographs:** No

**OSHA Regulated:** No

**Emergency and First Aid Procedures:**

**Inhalation:** First aid not normally required. If breathing difficulties develop remove to fresh air and provide oxygen if breathing is difficult.

**Ingestion:** If conscious give 1 - 2 glasses of water or milk and induce vomiting with Syrup of Ipecac, keeping head below hips to avoid aspiration into lungs. (Vomiting is most effective if initiated within 30 minutes of ingestion.) CONTACT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

**Skin Contact:** Wash area with soap and water. Remove contaminated clothing.

**Eye Contact:** Irrigate eyes immediately with large amounts of room temperature water for at least 15 minutes, or until eye is clear. TAKE TO A PHYSICIAN FOR HELP.

**SECTION VII - Precautions for Safe Handling and Use**

**Steps To Be Taken In Case Material Is Released Or Spilled:** Dike and contain spill with inert material (sand, sawdust, diatomaceous earth, etc.). Pump liquid into storage tanks. Remaining liquid may be taken up with inert materials. Place in closed container for proper disposal.

**Waste Disposal Method:** Dispose of in accordance with Local, State, and Federal regulations.

**Precautions To Be Taken In Handling And Storing:** Keep container closed and upright to prevent leakage. Avoid freezing or temperatures above 50<sup>0</sup> Celsius.

**Other Precautions:** Do not take internally. Keep away from children. Avoid breathing vapors. For external use only.

***SECTION VIII - Control Measures***

**Respiratory Protection (Specify Type):** None required in the absence of mist formation during spraying if good ventilation is maintained. Otherwise use NIOSH approved respirator designed to remove particles and vapor.

**Ventilation: Local Exhaust:** Needed at point of release to maintain exposure below TLV.  
**Mechanical General:** N/A  
**Special:** N/A  
**Other:** N/A

**Protective Gloves:** Rubber gloves for prolonged contact.

**Eye Protection:** Chemical splash goggles recommended to avoid eye contact.

**Other Protective Clothing or Equipment:** A rubber apron is recommended to protect clothing from splash during application.

**Work / Hygienic Practices:** Wash hands before eating.

***SECTION IX - Special Precautions***

**Other Precautions:** Do not apply to pavement during or just before (within one hour ) of a rain, to avoid contamination of runoff water.

***SECTION X - Disclaimer***

All information, recommendations, and suggestions concerning this product are based upon tests, literature references, and/or calculations, believed to be reliable. The manufacturer makes no guarantee, expressed or implied, as to the affect of use, or the safety and toxicity of the product. The information contained in this sheet cannot be taken as the sum total of all protective measures to be taken.